



Low-Velocity Hydronic Air Handlers

- Simplified installation
- Multi-speed ECM motor adjusts fan to maintain consistent air flow
- Independently select from up to 5 different fan speeds for heating and cooling
- Installer friendly front mount terminal blocks
- External pump & 24 VAC contacts
- Standard Domestic water priority
- Soft-ramping fan technology means quiet comfort in all modes of operation
- Lined with acoustic insulation
- Up to 3 tons of cooling and 100,000
 BTU of heating

Vulcano Compact Comfortable Comfort

THS 50-LV

THS 90-LV

Radiant Vulcano hydronic air handlers offer comfort solutions right "out-of-the-box". Integrated logic means simple plug and play installations that are right every time

 All Radiant air handlers match best with Radiant boilers, Radiant water heaters, or any other hot water source







Vulcano Low Velocity Premium Hydronic Air Handlers

Vulcano can accommodate:

- √ Central A/C
- **√** Humidifiers
- √ ERV's & HRV's
- √ Central Air Cleaners

All while utilizing conventional ducting systems in New Construction or Retrofit Applications.

Easy access front mount terminal blocks





Specifications

Model	THS 50-LV	THS 90-LV
Heating Performance Data @ 70°F Entering Air Temperature		
Max. MBTUH @ EWT 120°F	28	46
Max. MBTUH @ EWT 140°F	39	64
Max. MBTUH @ EWT 160°F	51	83
Max. MBTUH @ EWT 180°F	64	102
Piping Connections Copper (inches)	1/2	3/4
Flow Ratings GPM	4	5
CFM @ .5" E.S.P.	800	1,200
DX Cooling Tons	1 - 2	2 - 3
Cabinet Size W x D x H (inches)	14 x 21 x 29	21 x 21 x 29
Supply Air Opening Diameter (inches)	11.8 X 17.8	18.8 X 17.8
Return Air Opening W x H (inches)	18.3 x 14.3	18.3 x 14.3
Minimum Outlets	12	16
Maximum Outlets	17	23
Unit Weight (lbs.)	85	95





Thermal Hydronic Supply Ltd 101 Sharer Road Woodbridge ON L4L 8Z3 ph. 905-265-1527 fax 905-265-9739

